



1. Material  
 1.1: Housing: PA46 UL94-V0 Color: Nature.  
 1.2: Contact: C5191-H T=0.20±0.01.  
 1.3: LEG: C2680-H T=0.25±0.01.  
 2. Plating  
 2.1: Contact: Gold flash over Nickel.  
 2.2: LEG: Gold flash over Nickel.  
 3. Rating:  
 3.1: Operating Voltage: 50V AC/DC.  
 3.2: Current Rating: 0.5A AC/DC.  
 3.3: Operating Temperature: -40°C~+80°C.

PORT NO	Dimension			PORT NO	Dimension		
	A	B	D		A	B	D
04P	4.10	3.25	2.60	25P	14.60	13.75	13.10
05P	4.60	3.75	3.10	26P	15.10	14.25	13.60
06P	5.10	4.25	3.60	27P	15.60	14.75	14.10
07P	5.60	4.75	4.10	28P	16.10	15.25	14.60
08P	6.10	5.25	4.60	29P	16.60	15.75	15.10
09P	6.60	5.75	5.10	30P	17.10	16.25	15.60
10P	7.10	6.25	5.60	31P	17.60	16.75	16.10
11P	7.60	6.75	6.10	32P	18.10	17.25	16.60
12P	8.10	7.25	6.60	33P	18.60	17.75	17.10
13P	8.60	7.75	7.10	34P	19.10	18.25	17.60
14P	9.10	8.25	7.60	35P	19.60	18.75	18.10
15P	9.60	8.75	8.10	36P	20.10	19.25	18.60
16P	10.10	9.25	8.60	37P	20.60	19.75	19.10
17P	10.60	9.75	9.10	38P	21.10	20.25	19.60
18P	11.10	10.25	9.60	39P	21.60	20.75	20.10
19P	11.60	10.75	10.10	40P	22.10	21.25	20.60
20P	12.10	11.25	10.60	41P	22.60	21.75	21.10
21P	12.60	11.75	11.10	42P	23.10	22.25	21.60
22P	13.10	12.25	11.60	43P	23.60	22.75	22.10
23P	13.60	12.75	12.10	44P	24.10	23.25	22.60
24P	14.10	13.25	12.60	45P	24.60	23.75	23.10

宇詮實業有限公司  
 Onward Industry Co, Ltd.

UNLESS OTHERWISE SPECIFIED		APPROVED BY		DATE		TITLE	
TOLERANCES ARE		CHECKED BY		DATE		FPC 0.5Pitch 1.2H	
XX ±0.35						NON-ZIF connector.	
XXX ±0.15		DRAWN BY		DATE		DOCUMENT NO	
XXXX ±0.05							
ANG. ±0.30		UNIT		SIZE		REV	
		MM		A4		SCALE	
		SER		AREA		SHEET	
		DESCRIPTION		CHK		1/1	
		DATE		DATE		PAGE	
						1/1	
						SCALE	
						1:1	
						PAGE	
						1	
						A	