



FPC/FPC Insert Direction
 Recommended P.C.B Layout
 POB OTHERS TOLERANCES±0.05

- Note: 1:Material
 1.1: Housing: Thermoplastic,High temp, UL94-V0;
 1.2: Actuator: Thermoplastic,High temp, UL94-V0;
 1.3: Contact: Phosphor Bronze.
 1.4: LEG: Phosphor Bronze.
 2:Plating
 2.1: Contact:Matte Tin Or Gold Plating Nickel Overall.
 2.2: Matte Tin Plating Over Nickel.

No. of Contacts	Dimension				
	A	B	C	D	E
6	7.80	4.00	6.50	7.20	6.40
7	8.60	4.80	7.30	8.00	7.20
8	9.40	5.60	8.10	8.80	8.00
9	10.20	6.40	8.90	9.60	8.80
10	11.00	7.20	9.70	10.40	9.60
11	11.80	8.00	10.50	11.20	10.40
12	12.60	8.80	11.30	12.00	11.20
13	13.40	9.60	12.10	12.80	12.00
14	14.20	10.40	12.90	13.60	12.80
15	15.00	11.20	13.70	14.40	13.60
16	15.80	12.00	14.50	15.20	14.40
17	16.60	12.80	15.30	16.00	15.20
18	17.40	13.60	16.10	16.80	16.00
19	18.20	14.40	16.90	17.60	16.80
20	19.00	15.20	17.70	18.40	17.60
21	19.80	16.00	18.50	19.20	18.40
22	20.60	16.80	19.30	20.00	19.20
23	21.40	17.60	20.10	20.80	20.00
24	22.20	18.40	20.90	21.60	20.80
25	23.00	19.20	21.70	22.40	21.60
26	23.80	20.00	22.50	23.20	22.40
27	24.60	20.80	23.30	24.00	23.20
28	25.40	21.60	24.10	24.80	24.00
29	26.20	22.40	24.90	25.60	24.80
30	27.00	23.20	25.70	26.40	25.60

宇詮實業有限公司
 Onward Industry Co, Ltd.

SER	AREA	DESCRIPTION	CHK	DATE	UNIT	SIZE	DRAWING NO	REV	SHEET	SCALE
						A4	21-811-XXXX-5	A	1/1	1:1

UNLESS OTHERWISE SPECIFIED	TOLERANCES ARE	APPROVED BY	DATE	TITLE
XX	±0.25			FPC 0.8 Pitch 1.2H 掀蓋式
XXX	±0.15			
KXX	±0.05			
ANG	±0.30			